



DATASHEET



TRLED15

230V IP65 5ft 29W Single LED Non-Corrosive

www.mlaccessories.co.uk



MLA PART CODE	TRLED15
DESCRIPTION	230V IP65 5ft 29W Single LED Non-Corrosive
NET WEIGHT (KG)	2
FINISH	Grey
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1563 Height - 90 Width - 94
CONSTRUCTION	Construction - Polycarbonate
CLASS	I
IP RATING	IP65
WATTAGE (W)	29
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	3650
LUMENS LIGHT SOURCE ONLY (LM)	4040
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	142.29
CIRCUIT WATTAGE (W)	28.4
CCT	4000K
LIGHT COLOUR	Cool White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.129
DISPLACEMENT FACTOR	>0.9
SVM	0.828
PST-LM	0.035
BEAM ANGLE (DEGREES)	120
LIFE SPAN (HRS)	25,000
L70B50 LIFESPAN (HRS)	50,000

DIMMABLE	No
OPERATING TEMPERATURE	-20~35°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Compression gland
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 30W OUTPUT VOLTAGE - 32-43V OUTPUT CURRENT - 720mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 89.11% ISOLATION - SELV CASE TEMPERATURE (Tc) - 75°C
WARRANTY	5year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832970996

Date Created: 08/01/2024 14:36

