

Hilton NCF 5500K 1800mm (6ft) 65W Dimmable Emergency



Key Features

- Tridonic one4all Dimming - DALI 1 & 2 and switchDIM (Push)
- Emergency function
- IP65 rated housing
- Tamper-proof stainless steel clips
- Easy-mounting clips
- High lumens per watt

Key Data

Power	65W
Luminous Flux	8710lm
Colour Temperature	5500K
IP Rating	IP65
IK Rating	IK08

Dimensions	1800 x 125 x 88mm
Warranty	5 Years (Registration Required)

Technical Specifications

Colour Rendering	>80 CRI
Driver Output Voltage (DC)	30-42V
Fire Rating	V2
Flicker-Free	Yes
Hours Maintained	>3H
Input Voltage (AC)	220-240V
Lamp Viewing Angle	120°
LED Manufacturer	Honglitronic
LED Type	SMD 2835
Luminaire Efficacy	134lm/W
Luminous Flux Factor	5.10%
No. of LEDs	364
Operating Temp.	0°C to +45°C
Power Factor	>0.9
Self Test	No
Total Circuit Power (W)	65W +/- 5W
UGR Rating	More than 19
Weight	3.1Kg
Driver Manufacturer	Tridonic Premium Series
Electrical Class	1
Housing Colour	Grey
Housing Material	Polycarbonate
Lifespan LM80	43,000 Hours
Manufacturer	Sochii Lighting

Battery Pack	LiFePO4
Diffuser Material	Polycarbonate
Dimmable	Yes
Emergency Kit	3 Year Warranty
Emergency Operation	>3H
Emergency Pack	Streamer