



All New Media™ plates are suitable for use with standard euro module inserts. Selecting from a range of module inserts covering all manner of media transfer, the installer will now be able to configure their own arrangement of TV, radio or satellite reception, plus speaker, telephone and data outlets. All modules can be inserted into single or double wall plates, fitted onto standard switch and socket boxes.

20A Control Switches with Optional Flex Outlet

- CL022 20A DP Switch
- CL023 20A DP Switch With Neon

45A Switches

- CL200 45A 1 Gang DP Switch
- CL201 45A 1 Gang DP Switch With Neon
- CL202 45A 2 Gang DP Switch
- CL203 45A 2 Gang DP Switch With Neon

Fused Connection Units With Optional Flex Outlet

- CL049 3A Fused Connection Unit
- CL050 13A Fused Connection Unit
- CL051 13A DP Switched Fused Connection Unit
- CL051B 13A DP Switched Fused Connection Unit (No Knockouts)
- CL052 13A DP Switched Fused Connection Unit With Neon
- CL053 13A Fused Connection Unit With Neon

Lockable Switches

- CL660 20A Double Pole Key Lockable Switch
- CL660B 20A Double Pole Key Lockable Switch (No Knockouts)

Two keys provided (Spare keys available: SP660)

Telephone & Coaxial Socket Outlets

- CL120 Single Telephone Outlet - Master
- CL158 Single Isolated Coaxial Outlet

Isolated outlets will filter out any interference, if a 2 way signal is required, i.e. for use with satellite hard wire extensions, then a non-isolated outlet is required.

Lockable Sockets

- CL675 13A 1 Gang DP Key Lockable Socket With Neon
- CL675B 13A 1 Gang DP Key Lockable Socket With Neon (No Knockouts)

Two keys provided (Spare keys available: SP660)

Unfurnished Plates - New Media™

- CL311 1 Gang New Media™ Unfurnished Plate - 2 Apertures
- CL312 2 Gang New Media™ Unfurnished Plate - 4 Apertures

Standards: BS EN 60669-1 Fused Connection Units: BS 1363-4 BS 1362
Back Box Depth: 40mm Supplied 45A: 50mm Supplied
Cable Size: 3 x 2.5mm² or 2 x 4mm² 049: 4 x 2.5mm² or 2 x 4mm² 45A: 1 x 16mm² Knock-outs: 20mm
Dimensions: 1 Gang: 80mm (W) x 80mm (H) x 42mm (D) 2 Gang: 140mm (W) x 80mm (H) x 42mm (D)
200 201: 80mm (W) x 80mm (H) x 52mm (D) 202 203: 80mm (W) x 140mm (H) x 52mm (D)

Standards: 311 312: BS 5733 660 660B 675 675B: BS EN 60669-1 675 675B: BS 1363-2
Back Box Depth: 40mm Supplied 311 312: Dependent On Modules Fitted
Knock-outs: 20mm
Cable Size: 660 660B 675 675B: 3 x 2.5mm² or 2 x 4mm²
Dimensions: 1 Gang: 80mm (W) x 80mm (H) x 42mm (D) 2 Gang: 140mm (W) x 80mm (H) x 42mm (D)