

Technical Specification

Product Code: GM2018BKSB-FZ      Description: 20AX Double Pole Switch Module



General Information

|                         |  |
|-------------------------|--|
| Dimensions              | 24.5mm (W) x 50mm (H) x 22.5mm (D)   |
| Aperture Dimensions     | 20mm (W) x 35mm (H)  |
| Module Frame Finish     | Black  |
| Switch Finish           | Satin Brass  |
| Laser Etched Legend     | Freezer  |
| Materials               | Body & Insert: Nylon<br>Switch: Urea<br>Switch Cover: Stainless Steel<br>Terminals: Brass<br>Terminal Screws: Steel & Yellow Passivated<br>Contacts: Silver "on-lay" Copper / Brass  |
| Maximum Voltage         | 250V 50Hz  |
| Load Rating             | 20AX (Suitable For Inductive Loads)  |
| Terminal Size           | 5mmø   |
| Termination Type        | Screw  |
| Terminal Torque         | 1.2Nm  |
| Terminal Capacity       | 3 x 2.5mm² or 1 x 4mm²   |
| Product Markings        | Freezer  |
| Back Box Depth          | Dependent On Plate Used  |
| Operational Temperature | -5°C to +40°C  |
| Warranty                | 10 Years   |
| Standards               | BS EN 60669-1:2018   |
| Additional Information  | Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.<br>Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. |