

PRODUCT DATA SHEET

Hera Emergency Bulkhead 3W





EL3HBHE

PRODUCT DATA


PRODUCT CODE EL3HBHE LUMENS (Im) 150 WATTAGE (W) 3W COLOUR TEMP. (K) 6500K EMERGENCY YES WEIGHT (kg) 0.58kg BEAM ANGLE 120° CRI >80 DIMENSIONS (mm) 351x111x63mm EFFICIENCY (Im/w) 50Im/W IP IP65 WORKING ENVIRONMENT 5-45°C WARRANTY 4yr Warranty (2yr for Battery) TOTAL				
EMERGENCY YES WEIGHT (kg) 0.58kg BEAM ANGLE 120° CRI >80 DIMENSIONS (mm) 351x111x63mm EFFICIENCY (lm/w) 50lm/W IP IP65 WORKING ENVIRONMENT 5-45°C	PRODUCT CODE	EL3HBHE	LUMENS (Im)	150
BEAM ANGLE 120° CRI >80 DIMENSIONS (mm) 351x111x63mm EFFICIENCY (Im/w) 50Im/W IP IP65 WORKING ENVIRONMENT 5-45°C	WATTAGE (W)	3W	COLOUR TEMP. (K)	6500K
DIMENSIONS (mm) 351x111x63mm EFFICIENCY (Im/w) 501m/W IP IP65 WORKING 5-45°C	EMERGENCY	YES	WEIGHT (kg)	0.58kg
(mm) 351x111x63mm EFFICIENCY (Im/w) 50Im/W IP IP65 WORKING 5-ENVIRONMENT 45°C	BEAM ANGLE	120°	CRI	>80
IP IP65 ENVIRONMENT 45°C	351	(111x63mm	EFFICIENCY (Im/w)	50lm/W
WARRANTY 4yr Warranty (2yr for Battery)	IP	IP65		•
	WARRANTY 4yr W	arranty (2yr for Battery)		

KEY FEATURES

The 3W emergency bulkhead can be maintained (3 hour) or non-maintained, by adjusting the wiring setup (details available within the supplied instructions) and is compliant with EN 60598-1 &EN 60598-2. There are 20mm knockouts for easy cable management and a hinged gear tray for easy access COMMERCIAL APPLICATIONS

Public areas, workshops, warehouses, offices, carparks, service zones, corridors, schools, universities

POLAR CURVE DIAGRAM



DIMENSIONS

