

Product Code: SFBS504GY

Technical Specification

Luckinslive 435276218







Insert: Polycarbonate

Earth Strap: Mild Steel

Terminal Torque Value (Nm) 2.5

Switch Cover: Stainless Steel

Contacts: Silver "on-lay" Copper / Brass

General Information

Insert Dimensions (mm) 142.5 (W) x 82.5 (H) x 2.5 (D)

Plate Dimensions (mm) 146 (W) x 86 (H) x 4 (D)

Plate Fixing Centres - Horizontal (mm) 120.6

> Style Screwless Complete Finish Brushed Stainless

Insert Colour

Compatible Cover Plate SCP204#

> Materials Cover Plate: Stainless Steel

Rear Housing: Urea Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Anti Microbial Certified

Operating Voltage (AC) 250 Frequency (Hz) 50

Resistive Load Rating (A) 50 Termination Type Screw Terminal Size (mm) Ø6

Terminal Capacity - Solid (mm²) 1 x 16

Double Pole Switch Yes

> Twin Earth Terminals Yes

> > Product Marking Cooker

Minimum Back Box Depth (mm)

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

> Warranty (Years) 20

Standards BS 4177

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal







UK Design Registration: 3015621



Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362

Specification is subject to change without notice. Errors & Omissions excluded.

E: sales@scolmore.com | W: scolmore.com