

Product Code: SFBK038BK

Description: 5A Round Pin Socket Outlet

Technical Specification

Luckinslive 435279354







General Information

Insert Dimensions (mm) 82.5 (W) x 82.5 (H) x 2.5 (D)

Plate Dimensions (mm) 86 (W) x 86 (H) x 4 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Screwless Complete

Finish Matt Black Insert Colour Black

Compatible Cover Plate SCP238#

> Cover Plate: Polycarbonate Materials Insert: Polycarbonate

Rear Housing: Nylon Terminals: Brass Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Anti Microbial Certified

Operating Voltage (AC) Frequency (Hz) 250

Resistive Load Rating (A) 5 Termination Type Screw

Terminal Size (mm) Ø5 Terminal Torque Value (Nm) 1.2

Terminal Capacity - Solid (mm²) 4 x 1.5 or 3 x 2.5

Switched No

Twin Earth Terminals

Minimum Back Box Depth (mm)

Ingress Protection Operational Temperature (°C) -5 to +40

Warranty (Years)

Standards BS 546

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal











Specification is subject to change without notice. Errors & Omissions excluded.