

Product Code: CSP031

Luckinslive 422559883

Description: Smart Window & Door Sensor



UK PS&TI



General Information

Magnet Dimensions (mm)	26 (L) x 10 (W) x 9 (D)	
Transmitter Dimensions (mm)	40 (L) x 25 (W) x 14.5 (D)	
Materials	Housing: Polycarbonate	Electronics: PCB & Electronic Components
Operating Voltage (DC)	3	
Battery Type	CR 2032 (Supplied)	
Battery Lifetime (Approx.)	1 Year (Dependent On Use)	
Protocol	Zigbee	Signal Transmission Frequency 2.4GHz
Activation Distance (mm)	10 - 20 (Between Sensor & Magnet)	
Indicator Colour	Blue	
Ingress Protection	IP20	
Working Humidity	0%-95%RH (Non-condensing)	
Operational Temperature (°C)	-10 to +50	
Warranty (Years)	3	

Standards BS EN 60950-1, BS EN 55035, BS EN 61000-3-2, BS EN 61000-3-3, BS EN 62311

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Control linked receivers through the ClickSmart+ app
Send activation alerts to your phone

Components Supplied Smart Window & Door Sensor, Reset Key, Instruction Manual

Installation Overview Suitable for doors or windows.
Self-adhesive pads applied ready for installation.

Programming Information With hub and app setup with sensor having battery installed, using the pin supplied press the reset button for five seconds and the sensor LED will start flashing. Can be paired with hub via app.

