

Installation contactor, 20A, 230V AC, 2NC

Part no. **CR2002230A**
135170



Product name	Eaton Distribution parts
Part no.	CR2002230A
EAN	8711426104037
Product Length/Depth	75 millimetre
Product height	80 millimetre
Product width	18 millimetre
Product weight	0.133 kilogram
Compliances	RoHS conform
Product Tradename	None
Product Type	Distribution parts
Product Sub Type	None
Public Consumption	Yes
Product Family Description	ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable	Yes
Amperage Rating	20 A
Built-in depth	60 mm
Degree of protection	IP20
Features	Additional equipment possible
Incandescent lamp load - max	1950 W
Load fluorescent lamp (duo circuit) - max	1160 V-A
Load fluorescent lamp (parallel compensated) - max	232 V-A
Load fluorescent lamp - max	910 V-A
Number of contacts (normally closed contacts)	2
Number of contacts (normally open contacts)	0
Number of modular spacings	1
Rated operating voltage (Ue) - max	400 V
Rated operating voltage (Ue) - min	400 V
Utility category	1
Utilization category (according to EN IEC 60947-4-1)	AC-1
Voltage rating (excitation) - max	253 V
Voltage rating (excitation) - min	195.5 V
Voltage type	AC

Technical data ETIM 8.0

Devices for distribution board-/surface mounting (EG000062) / Installation contactor for distribution board (EC001653)			
Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Installation contactor for distribution board (ecl@ss10.0.1-27-14-23-08 [AFZ820015])			
Rated operating voltage	V	400 - 400	
Rated operation current	A	20	
Utility category		1	
Rated excitation voltage	V	195.5 - 253	
Voltage type (operating voltage)		AC	
Voltage type (excitation voltage)		AC	
Number of contacts as normally open contact		0	
Number of contacts as normally closed contact		2	
Max. incandescent lamp load	W	1,950	
Max. load fluorescent lamp	VA	910	

Max. load fluorescent lamp (Duo circuit)	VA	1,160
Max. load fluorescent lamp (parallel compensated)	VA	232
Slider for hand switch		No
Width in number of modular spacings		1
Built-in depth	mm	60
Additional equipment possible		Yes
With day/night function		No
Hum-free		No
Degree of protection (IP)		IP20