

Product Code: APDSSWKP

Description: Singleway Video Door Station with Keypad



General Information

Dimensions (mm)	200 x 87 x 53
Materials	Aluminium Alloy
Mounting	Surface & Flush (requires APDSKPFMS) Mounted
Weight (Kg)	.64
Warranty (Years)	3

Media Information

Illumination	5 White light LEDs
Sensitivity (Lux)	0.1
Sensor Size (")	1/3
Lens size (mm)	3.6
Audio	Full Duplex

Programming

User Interaction	0 - 9, *, #, and Bell
Code lengths	2 - 6
Maximum Access Codes	10 PINs

Environment

Ingress Protection	IP55
Operating Temperature (°C)	-20 to +40

Supplied Fixing Screws, and Wall Plugs, User Manual

Features

Outdoor Station rings so that the user knows whether the call has been answered, calls last up to 30 seconds

Supply & Power

Operating Voltage (V DC)	24 (BUS)
Global Selections	Normally Open or Normally Closed; Volt-Free or 12V DC300mA
Effective Distance to PowerSupply (M)	50
Lock outputs	2

Network

Recommended BUS Cable	Cat5e or higher
Communication Protocol	BUS

Accessories

EVBPSBB: 12V Lock power supply with battery backup
 APPOWSWDR: Din Mounted BUS power supply
 APMONW: Aperta BUS Monitor in white
 APMONB: Aperta BUS Monitor in Black
 APMONWG: Aperta GUI BUS Monitor in white
 APMONBG: Aperta GUI BUS Monitor in Black
 APAUDH: Aperta BUS Audio Only Handset in White
 APAUDHBLK: Aperta BUS Audio Only Handset in Black
 ENTERD: Flush Electric Lock
 ENTERD-YLR: Surface Electric Lock
 APDSKPFMS: Flush mount kit for APDSMW, APDSSWKP and APDSPXMW

Additional Information Simple 2-core Installation
 High-Resolution Colour Camera

