

Technical Specification



Product Code: MP603SBBK

Luckinslive 425339259

Description: New Media™ Part Furnished Front Plate - 2 x 13A DP Switched Socket Outlets & 3 Apertures





General Information

Plate Dimensions (mm)	250 (W) x 86 (H) x 8 (D)	
Dimensions With Gasket (mm)	254 (W) × 90 (H) × 9 (D)	
New Media Aperture Dimensions (mm)	75 × 50	
New Media Module Quantity	Accepts Upto 3 x 25mm x 50mm Module	29
Style	Deco	
Finish	Satin Brass	
Insert Colour	Black	
Gasket Colour	Black	
Materials	Front Plate: Stainless Steel	Insert, Rear Housing & Rocker Switch: Urea
hadhad	Terminals: Brass	Terminal Screws: Steel & Yellow Passivated
	Contacts: Silver "on-lay" Copper / Brass	Internal Busbars: Formed Pressed Brass
	Earth Strap: Mild Steel	
Anti Microbial Certified	No	
Operating Voltage (AC)	250	Frequency (Hz) 50
Resistive Load Rating (A)	13	
Termination Type	Screw	
Terminal Size (mm)	Ø5 Ter	minal Torque Value (Nm) 2.5
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4	
Double Pole Switch	Yes	
Twin Earth Terminals	Yes	
Yoke Required	No	
Compatible Back Box (mm)	MP520 (47)	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	20	
Standards BS 1363-2		
Standlus DS 1303-2		

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Requires MP520 flush back box. Interchangeable with modules in the New Media Range.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com









UK Design Registration: 3015621

