

## H2 Pro

Fixed fire-rated, colour and lumen switchable downlight with easy-fit connector

### Features

IP rating	IP65
CSP Switchable	CCT Switchable
Tiltable	No
UGR	28
Dimmable Option	Yes
LED Lifetime	70,000h L70
CRI	80 Ra
SDCM	3 SDCM
Emergency Option	Yes

### Installation information

Install Connector Type	Easy-fit connector
Insulation Coverable	All insulation
Cut Out Size	Ø 64-72mm
UK Bathroom Zone	1
Inrush Current	1A 7.5ms
Construction Material	Mild steel / V0 rated plastic
Maximum ceiling thickness	40 mm
Weight	270g
Maximum Ambient Temperature	40°C
SELV	Yes
UK Building Regulations	Part B, C, E, P & L
Ceiling Joist Approvals	Solid timber, I-Joist and Metal Web
Electric Class (1, 2, 3)	2

### Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
DLE5245500	Bezel sold separately	5W	2700K	55°	550	110	554
DLE5245500	Bezel sold separately	5W	3000K	55°	650	130	654
DLE5245500	Bezel sold separately	5W	4000K	55°	650	130	654
DLE5245500	Bezel sold separately	7W	2700K	55°	750	107	755
DLE5245500	Bezel sold separately	7W	3000K	55°	850	121	856
DLE5245500	Bezel sold separately	7W	4000K	55°	850	121	856
DLE5245500EM	Bezel sold separately	5W	2700K	55°	550	110	554
DLE5245500EM	Bezel sold separately	5W	3000K	55°	650	130	654
DLE5245500EM	Bezel sold separately	5W	4000K	55°	650	130	654
DLE5245500EM	Bezel sold separately	7W	2700K	55°	750	107	755
DLE5245500EM	Bezel sold separately	7W	3000K	55°	850	121	856
DLE5245500EM	Bezel sold separately	7W	4000K	55°	850	121	856

Product not suitable for exterior use, please use H2 Pro Extreme.



01604 495 151  
collingwoodlighting.com

collingwoodled  
 /collingwoodlighting  
 collingwoodlighting

### Guarantee

7 year extended warranty

### Features & benefits

Colour switchable between 2700K, 3000K and 4000K

High efficacy of 130lm/W

Insulation coverable

Wattage switchable between 5W and 7W

Compatible with Collingwood smart system

Quick and easy installation with easy-fit connector

Integrated emergency option available

Compatible with twist and lock bezels



2 part, push fit, loop in/ loop out connector

Fixed position downlight

Light source energy efficiency:



Beam angle: 55°



Wiring information

Cable / Flying Lead	0.15m
Cable Required for Connector	Push-fit terminal for: Twin & Earth (6242Y 2x1.5mm <sup>2</sup> ) or 3-core cable (R02V 3x1.5mm <sup>2</sup> )
Type of Wiring Required	Parallel

LED driver

N/A (integrated SELV driver)	220-240V	N/A	Yes	N/A	N/A	N/A
------------------------------	----------	-----	-----	-----	-----	-----




Accessories

H2 Bezels	Twist and lock bezels	Sold Separately
DLCONVERT70	Downlight Converter Plate	Sold Separately
DLCVT110	Downlight Converter Plate	Sold Separately
DM298FP	Faceplate Dimmer	Sold Separately
DM298GRID	Grid Dimmer	Sold Separately



collingwood

01604 495 151  
collingwoodlighting.com

-  collingwoodled
-  /collingwoodlighting
-  collingwoodlighting

H2 Pro

The H2 Pro downlight is one of a kind. The lumen output and the colour temperature can be changed via switches on the driver. This flexibility is valuable and offers peace of mind that you have a downlight that is capable of fulfilling the requirements of the majority of installations. The H2 Pro has a 7 year extended warranty, along with 70,000 hours of LED lifetime, it is a fit and forget solution.