Ei630iRF



RadioLINK+ Heat Alarm



- Heat sensor responds to heat build-up from large flaming fires (triggers at 58°C)
- AudioLINK+ data extraction technology
- 10 year Lithium battery powered
- RadioLINK+ Wireless interconnection
- Kitemarked to BS 5446-2:2003
- 5 year guarantee





Description

The Ei630iRF RadioLINK+ Heat Alarm is powered by a 10 year life sealed in Lithium cell. It is able to wirelessly interconnect with any other RadioLINK products and also features a large test button and twist on base with an anti-tamper locking option

Technical

Sensor Type	Heat (A1)	RF Frequency (MHz)	868.499
RF Range (m)	>100 in free air	Indicators	Red - Power Up, Alarm, Silence Mode, Fault / Blue - RF transmission
Battery Type	Lithium primary	Technologies	AudioLINK+/RadioLINK+
Dimensions & Weights			
Depth (mm)	64	Height (mm)	122
Width (mm)	122	Product weight (kg)	0.203
Packaged weight (kg)	0.259		
Approvals & Warranty			
Certification/Approvals	BS 5446-2:2003 / EN 300 220-1 / EN 301 489-1	Warranty	5 year warranty

EAN Number

Environmental

Humidity Range (%) 15-95

Temperature Range (°C) -10 to 40

01691 664100 E enquiries@aico.co.uk

W www.aico.co.uk

Company Registration No.: 2544399 WEEE Registration No.: WEE/AE0109WY Battery Producer Registration No.: BPRN00307

5099383010275

