

## WL070

Straight to mains up / down LED wall light



**Guarantee / Warranty:** 7 year extended warranty available

### PHOTOMETRICS @ 25°C

| Product Code | Finish | Wattage | Colour | Beam Angle | lm          | lm/W | lx at 1m    |
|--------------|--------|---------|--------|------------|-------------|------|-------------|
| WL070BNBM40  | Black  | 5.1W    | 4000K  | 12°        | 560* / 280* | 110  | 3455 / 1727 |
| WL070BNBM30  | Black  | 5.1W    | 3000K  | 12°        | 550* / 275* | 108  | 3394 / 1697 |
| WL070BNBM27  | Black  | 5.1W    | 2700K  | 12°        | 510* / 255* | 100  | 3147 / 1573 |
| WL070ZNBM40  | Bronze | 5.1W    | 4000K  | 12°        | 560* / 280* | 110  | 3455 / 1727 |
| WL070ZNBM30  | Bronze | 5.1W    | 3000K  | 12°        | 550* / 275* | 108  | 3394 / 1697 |
| WL070ZNBM27  | Bronze | 5.1W    | 2700K  | 12°        | 510* / 255* | 100  | 3147 / 1573 |
| WL070CNBM30  | Copper | 5.1W    | 3000K  | 12°        | 550* / 275* | 108  | 3394 / 1697 |
| WL070CNBM27  | Copper | 5.1W    | 2700K  | 12°        | 510* / 255* | 100  | 3147 / 1573 |
| WL070SNBM40  | Silver | 5.1W    | 4000K  | 12°        | 560* / 280* | 110  | 3455 / 1727 |
| WL070SNBM30  | Silver | 5.1W    | 3000K  | 12°        | 550* / 275* | 108  | 3394 / 1697 |
| WL070SNBM27  | Silver | 5.1W    | 2700K  | 12°        | 510* / 255* | 100  | 3147 / 1573 |

\*Combined total from both sets of LED | \*Per module


### INSTALLATION INFORMATION

|                          |                                                                    |
|--------------------------|--------------------------------------------------------------------|
| Input                    | 220-240V 50/60Hz                                                   |
| Dimmable                 | No                                                                 |
| Inrush current           | 60A 0.037ms                                                        |
| Construction material    | Silver, Black & Bronze: anodised aluminium<br>Copper: solid copper |
| Weight                   | Silver: 900g<br>Black: 900g<br>Bronze: 900g<br>Copper: 2500g       |
| Class                    | Class I                                                            |
| Max. ambient temperature | 40°C                                                               |

### BENEFITS

- Bi-directional, straight to mains wall light, perfect for framing entrances and illuminating columns
- Long lifetime of 70,000 hours
- Single LED and lens combination for maximum efficiency and optimal light distribution
- Suitable for coastal areas

### SIZE DIAGRAM



### ACCESSORIES

|     |                         |
|-----|-------------------------|
| N/A | No accessories required |
|-----|-------------------------|

Silver

Black

Copper

Bronze