

GL018 C

0.5W, 3lm mini marker ground light



Guarantee / Warranty: 3 year guarantee | GL018 C WW / GL018 C 27: 7 year extended warranty available



PHOTOMETRICS @ 25°C

Product Code	Wattage	Colour	Wattage	Beam Angle	lm	lm/W	lx at 1m
GL018 C NW	0.5W	4000K	0.5W	120°	3	6	1
GL018 C WW	0.4W	3000K	0.4W	120°	4	10	1
GL018 C 27	0.4W	2700K	0.4W	120°	4	10	1
GL018 C BLUE	0.5W	Blue	0.5W	120°	1	2	1


INSTALLATION INFORMATION

Input	24V DC
Dimmable	Requires PDCINT1-10V
Cut-out size	Ø28mm
Construction material	Stainless steel (316)
Weight	300g
Class	Class III
Max. ambient temperature	35°C

BENEFITS

- Frosted effect for softer tone of light
- Low profile for easy installation
- Robust cable for outdoor use
- Parallel wiring for easier installation and more fittings to a power supply
- Suitable for coastal areas

SIZE DIAGRAM



ACCESSORIES

JB1 / JB5 / JB6 IP68 waterproof connectors

PDCINT1-10V 1-10V dimming interface for use with 24 LED drivers

GL018 C AB

0.5W, 3lm mini marker ground light



Guarantee / Warranty: 3 year guarantee | GL018 AB WW: 7 year extended warranty available



PHOTOMETRICS @ 25°C

Product Code	Wattage	Colour	Beam Angle	lm	lm/W	lx at 1m
GL018 C AB NW	0.5W	4000K	120°	3	6	1
GL018 C AB WW	0.4W	3000K	120°	4	10	1
GL018 C AB 27	0.5W	2700K	120°	3	6	1
GL018 C AB BLUE	0.5W	Blue	120°	-	-	-


INSTALLATION INFORMATION

Input	24V DC
Dimmable	Requires PDCINT1-10V
Cut-out size	Ø28mm
Construction material	Brass
Weight	300g
Class	Class III
Max. ambient temperature	35°C

BENEFITS

- Frosted effect for softer tone of light
- Robust cable for outdoor use
- Shallow depth for easy installation
- Solid brass for antique effect
- Parallel wiring for easier installation and more fittings to a power supply
- Suitable for coastal areas

SIZE DIAGRAM



ACCESSORIES

JB1 / JB4 / JB6 IP68 waterproof connectors

PDCINT1-10V 1-10V dimming interface for use with 24 LED drivers