

Product Code: SFBS535PW

## **Technical Specification**

Luckinslive 435284200

Description: 13A Ingot 1 Gang Double Pole Switched Socket Outlet







Insert: Polycarbonate

Terminal Torque Value (Nm) 2

Switch Cover: Stainless Steel

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

## **General Information**

Insert Dimensions (mm) 82.5 (W) x 82.5 (H) x 2.5 (D)

Plate Dimensions (mm) 86 (W) x 86 (H) x 4 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Screwless Complete Finish Brushed Stainless

Insert Colour Polar White Compatible Cover Plate SCP435#

Materials Cover Plate: Stainless Steel

Rear Housing: Urea

Terminals: Brass

Contacts: Silver "on-lay" Copper / Brass

Earth Strap: Mild Steel

Anti Microbial Certified Frequency (Hz) 50 Operating Voltage (AC) 250

Resistive Load Rating (A) 13 **Termination Type** Screw

Terminal Size (mm) Ø5

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Double Pole Switch Yes Minimum Back Box Depth (mm)

Ingress Protection IP20 Operational Temperature (°C) -5 to +40

Warranty (Years)

Standards BS 1363-2

## **Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.









Specification is subject to change without notice. Errors & Omissions excluded.