

Technical Specification

Product Code: SFBS142PL Description: 2 Gang Unfurnished Dimmer Plate- 2 Apertures Luckinslive 435277055





General Information

Insert Dimensions (mm) Plate Dimensions (mm) Plate Fixing Centres - Horizontal (mm) Style Finish Compatible Cover Plate Materials	82.5 (W) x 82.5 (H) x 2.5 (D) 86 (W) x 86 (H) x 4 (D) 60.3 Screwless Complete Brushed Stainless SCP242# Cover Plate: Stainless Steel Terminals: Brass	Insert: Polycarbonate Terminal Screws: Steel & Yellow Passivated
	Earth Strap: Mild Steel	Terminal Screws. Steel & Tellow Fassivaled
Anti Microbial Certified	No	
Minimum Back Box Depth (mm)	35	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	20	

Standards BS 5733

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

The safety shutter will only fully open when all three BS 1363 plug-top pins engage correctly with the shutter. Inserting the earth pin alone will not open the live and neutral shutter like conventional socket shutters.

Compatible Dimmer Modules MD9014: 100W Dual Mode LED Dimmer Module MDg001: 6A Push ON/OFF (Dummy Dimmer / Non Dimmable) Module MD9010: 1-10V Analogue Rotary Dimmer Module

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com









UK Design Registration: 3015621

