

Combination Plates

RCD PROTECTED
13 AMP
FLUSH

FILTERED
13 AMP
FLUSH

13 AMP
FLUSH



K2746D1WHI



K6211WHI



K6300WHI



K1816WHI



K2741WHI



K2746D1RED



K6231WHI



K6303WHI



K1826WHI



K2740WHI



K2746D2WHI



K6233WHI



K1800WHI

- K2746D1WHI** 10
2 GANG DP
WITH RED OUTBOARD ROCKERS
AND DUAL EARTH TERMINALS
- K2746D1RED** 10
2 GANG DP
WITH RED OUTBOARD ROCKERS,
NEONS AND DUAL EARTH TERMINALS
- K2746D1WHI** 10
2 GANG DP
WITH RED OUTBOARD ROCKERS,
NEONS AND DUAL EARTH TERMINALS
- K2746D1RED** 10
2 GANG DP
WITH RED OUTBOARD ROCKERS,
NEONS AND DUAL EARTH TERMINALS
- K2746D2WHI** 10
2 GANG DP
WITH GREEN OUTBOARD ROCKERS
AND DUAL EARTH TERMINALS

- K6211WHI** 1
2 GANG
10mA RATED TRIPPING CURRENT
ACTIVE CONTROL CIRCUIT
- K6231WHI** 1
2 GANG
30mA RATED TRIPPING CURRENT
ACTIVE CONTROL CIRCUIT
- K6233WHI** 1
2 GANG
30mA RATED TRIPPING CURRENT
PASSIVE CONTROL CIRCUIT

- K6300WHI** 1
1 GANG
30mA RATED TRIPPING CURRENT
ACTIVE CONTROL CIRCUIT
- K6303WHI** 1
1 GANG
30mA RATED TRIPPING CURRENT
PASSIVE CONTROL CIRCUIT

- K1816WHI** 1
2 GANG DP
SPIKE
- K1816KOWHI** 1
2 GANG DP
SPIKE WITH
TAMPERPROOF SCREW
- K1826WHI** 1
2 GANG DP
SPIKE AND RFI
- K1826KOWHI** 1
2 GANG DP
SPIKE AND RFI WITH
TAMPERPROOF SCREW
- K1800WHI** 5
REPLACEMENT FILTER CASSETTE

- K2741WHI** 1
2 GANG DP
COMBINATION PLATE WITH
4 X EURO APERTURE
- K2740WHI** 1
4 GANG DP
COMBINATION PLATE WITH
TV/FM/DAB/SAT X 2 QUAD,
TV, TELEPHONE AND
4 X EURO APERTURE

For sockets complying with Medical Electrical Installation Guidance Notes (MEIGaN), see page 158

MOUNTING BOXES:
FLUSH: 862ZIC (25mm)
FLUSH: 886ZIC (35mm for extra wiring space)
SURFACE: K2142WHI

K2746 and K2746D1 are fitted with two earth terminals to provide a double earth facility for use when installations require a high integrity protective connection as specified within BS 7671: 2008.

MOUNTING BOXES:
FLUSH: 886ZIC – 35mm deep
SURFACE: K2140WHI – 30mm deep
Earth pin operated shutter.

These a.c. and pulsating d.c. fault current sensitive products have up to 15mm thick frontplates and are suitable for boxes with 30mm min. depth and supply voltages of 240V 50Hz.

A 25mm deep box (862ZIC) can be used but conduit entry is restricted.

Refer to Sentrysocket section, page 292, for more information on active and passive control circuits.

DIMENSIONS: 86 x 146mm
FIXING CENTRES: 120.6mm
BS 7288: 1990

All units are a.c. and pulsating d.c. fault current sensitive devices.
Maximum total load 13A

MOUNTING BOXES:
FLUSH: 886ZIC
SURFACE: K2172WHI

K1816 provides filtering to reduce voltage spikes only.

K1826 provides two way filtering to reduce voltage spikes and radio frequency interference on the mains. Protected by thermal cut-out.

BS 5733: 2010

MOUNTING BOXES:
FLUSH 35mm
2 GANG: 857ZIC*
4 GANG: 853ZIC*
FLUSH 47mm
2 GANG: 858ZIC*
4 GANG: 854ZIC*

*Provides segregation between power and TV/FM/SAT/DAB/Euro Module sections