

## **Technical Specification**

Product Code: GM2018BTPW

Luckinslive 407676891

Description: 20AX Double Pole Switch With Blue LED Indicator Module



## **General Information**

Dimensions (mm)	24.5 (W) x 50 (H) x 22.5 (D)	
Colour	Polar White	
Insert Colour	Blue LED	
Switch Finish	Polar White	
Materials	Transparent Trim: Polycarbonate	Switch: Urea
	Rear Housing: Nylon	Terminals: Brass
	Terminal Screws: Steel & Yellow Passivated	d Contacts: Silver "on-lay" Copper / Brass
Anti Microbial Certified	No	
Operating Voltage (AC)	250	Frequency (Hz) 50
Inductive Load Rating (AX)	20	
Load Rating Comments	Suitable for Fluorescent or Inductive Loads	
Termination Type	Screw	
Terminal Size (mm)	Ø5 Tern	ninal Torque Value (Nm) 1.2
Terminal Capacity - Solid (mm <sup>2</sup> )	3 × 2.5, 2 × 4	
Double Pole Switch	Yes	
LED Indicator	Yes	Indicator Colour Blue
Minimum Back Box Depth (mm)	25 (35 Flat Plate)	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	20 Warra	nty - Electronics (Years) 2
Standards BS EN 60669-1		

## **Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com UK Patent: GB 2578427











Specification is subject to change without notice. Errors & Omissions excluded. Page 1 of 1 (19-04-24)