



AOSLED/3M/ST

Osprey High Rack LED Bulkhead 9W Maintained / Non-Maintained



Features

Modern slim profile LED polycarbonate bulkhead

Compact high polished reflector design to provide required light level from high mounting heights

High performance LED's and optical performance allows increased spacing ratios

Cold store option incorporates an intelligent integral heat management system to operate in cold store applications down to -30°C

Self-test as standard

Aesthetically designed for modern appearance

20mm side and rear cable entries

General Information

Lamp Type	LED
Colour / Finish	White
Self Test	Yes
IP Rating	IP65
Class Protection	1
Internal / External	Internal
Surface / Recessed / Suspended	Surface
Warranty (Years)	3
CE Mark	Yes
Length (mm)	330
Width (mm)	135
Height (mm)	69
Accessories	ASBP/15

Technical Information

Wattage	9W
Lumens Delivered	380lm (Emergency), 438lm (Standard)
CCT	6500K
Input	230V
Hertz	50/60Hz
Operating Temp	0C° to 45C°

Technical Data - ETIM 6 - Emergency luminaire (EC001957)

Mounting method	Wall surface mounted
With light source	Yes
Lamp power	9 W
Material housing	Plastic
Colour housing	White
Type of indicator	Only single-sided
Monitoring equipment	Automatic self test
Nominal voltage	230-230 V
Protection class	I
Degree of protection (IP)	IP65
Length	330 mm
Width	135 mm
Height/depth	69 mm
Luminous flux at emergency operation	380 lm
Rated luminous flux acc. IEC 62722-2-1	438 lm
Colour of light	White
Colour temperature	6500-6500 K

Datasheet generated from <https://www.electrika.com> last updated Friday, June 7, 2019 12:33:27 PM

