

with screw terminals







Weekly time switch 1 channel, 3 modules with reserve

Technical characteristics

Architecture	
Fixing mode	Din-Rail
Functions	
Power reserve	≈ 200 h
Configuration	
Switch mode	change-over contact, usable as NC or NO
Switch mode	change-over contact, usable as NC of NO
Main electrical features	
Rated operational voltage Ue	230 / 240 V
Frequency	50-60 Hz
Dimensions	
Depth of installed product	60 mm
Height of installed product	90 mm
Width of installed product	54 mm
Power	
Power consumed	0.5 VA
Power consumption (operation)	0.5 VA
Total power loss under IN	1 W
Power dissipation per coil	0.5 W
Battery	
Charging time of the power reserve in hours	120
Incandescent bulbs control	
Max. power with incandescent lamps	900 W
Installation, mounting	
Mounting type	din-Rail
Connection	
Connection cross-sect. flexible conductor	1 / 4mm²
Connection cross-sect. rigid cable	1 / 4mm²
Type of connection	with screw
Number of contacts	1
Type of contacts	1 changeover

Type of connection

Settings	
Summer / Winter time change	manual
Shortest switching time	120 mr
Type of programming	analog
Programming cycle	1X7D.
Setting	Fine setting of time via rotating hand
Equipment	
Number of channels	1
Supply failure reserve	120 h
Use	
Cycle	weekly
Safety	
Protection index IP	IP20
Use conditions	
Operating temperature	-1055 °C
Working accuracy	1