

# ActiV Conventional Hi-Output W-2.75-9 Wall VAD c/w Voice Sounder (shallow base)

Part No. **BF447C/CC/SR**



## Overview

Provides 'W-2.75-9' rated light distribution when wall mounted (min. 0.4 lux over a 2.75x 9m cuboid area). Can also be used as a W-4-4 VAD.

Superb sound intelligibility.

Choose from two evacuation voice messages and four evacuation alarm tones (your selected evacuation message will be preceded by the selected tone).

Three selectable VAD flash rates (0.5Hz, 1Hz, OFF)

Alarm Current at 30Vdc = 17mA (0.5Hz) or 24mA (1Hz)

Alarm Current at 18Vdc = 18.5mA (0.5Hz) or 30mA (1Hz)

IP21C rated.

Manufactured in the UK by C-TEC.

## Technical Specifications

Protocol/compatibility	Compatible with C-TEC's CFP, FP, MFP and EP203 conventional fire alarm panels and virtually all other makes (testing on third-party panels is recommended before use)
Application/operation	Designed to be wall mounted. Indoor areas only.
VAD category & coverage	W-2.75-9 rated light distribution (min. 0.4 lux over a 2.75m x 9m cuboid area). Can also be used as a W-4-4 VAD.
Flash rate & colour	0.5Hz; 1Hz or OFF / White.
Supply/operating voltage	18 to 30V DC.
Alarm current	At 30Vdc: 17mA (0.5Hz) or 24mA (1Hz); At 18Vdc: 18.5mA (0.5Hz) or 30mA (1Hz)
Product dimensions (mm)	108mm diameter x 99mm deep.
IP Rating	IP21C (Type A).
Weight	230g.
Operating conditions/temperature	-10°C to +55°C. Max. 95% RH (Non-condensing).



T 01942 322744 E sales@c-tec.co.uk  
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom