



HMF199T

MCBs 80 - 125A 10kA C Curve

Curves C

10 kA BS EN 60898-1
10 kA BS EN 60947-2

I_n 80 to 125A

Tripping Curves

"C" magnetic setting between
5 to 10 I_n .

Use

Commercial and industrial
applications.

Connection Capacity

- 35mm² flexible wire (50mm² possible with some cable pin lugs)
- 70mm² rigid wire

KEMA

Approved according to
BS EN 60898-1.



HMF299T

Single Pole MCBs 10kA C Curve

Rating	Width (26.25mm)	Cat ref.
80A	1 ½ Mod	HMF180T
100A	1 ½ Mod	HMF190T
125A	1 ½ Mod	HMF199T



HMF399T

Double Pole MCBs 10kA C Curve

Rating	Width (52.5mm)	Cat ref.
80A	3 Mod	HMF280T
100A	3 Mod	HMF290T
125A	3 Mod	HMF299T

Triple Pole MCBs 10kA C Curve

Rating	Width (75.75mm)	Cat ref.
80A	4 ½ Mod	HMF380T
100A	4 ½ Mod	HMF390T
125A	4 ½ Mod	HMF399T



HMF499T

Four Pole MCBs 10kA C Curve

Rating	Width (105mm)	Cat ref.
80A	6 Mod	HMF480T
100A	6 Mod	HMF490T
125A	6 Mod	HMF499T