

Product Code: GM2018BKMB-OV

Luckinslive 435284857

Description: 20AX Double Pole Switch Module



### General Information

Dimensions (mm)	24.5 (W) x 50 (H) x 22.5 (D)		
Finish	Matt Black		
Insert Colour	Black		
Switch Finish	Matt Black		
Materials	Body & Insert: Nylon	Switch: Urea	
	Switch Cover: Stainless Steel	Terminals: Brass	
	Terminal Screws: Steel & Yellow Passivated	Contacts: Silver "on-lay" Copper / Brass	
Anti Microbial Certified	No		
Operating Voltage (AC)	250	Frequency (Hz)	50
Inductive Load Rating (AX)	20		
Load Rating Comments	Suitable for Fluorescent or Inductive Loads		
Termination Type	Screw		
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm)	1.2
Terminal Capacity - Solid (mm <sup>2</sup> )	3 x 2.5 or 2 x 4		
Double Pole Switch	Yes		
Product Marking	Oven		
Minimum Back Box Depth (mm)	25 (35 Flat Plate)		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

**Standards** BS EN 60669-1

### Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

UK Patent: GB 2578427

Scolmore House, Mariner, Lichfield Road Industrial Estate,

Tamworth, Staffordshire, B79 7UL United Kingdom

T: +44 (0)1827 63454 | F: +44 (0)1827 63362

E: sales@scolmore.com | W: scolmore.com



Catalogue



Range



DoC



Installation

