



Technical Specification

Product Code: MD023PN-HT

Description: 20A Ingot Double Pole Switch With Neon Module





General Information

Additional Information	Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
Standards	BS EN 60669-1:1999 +A1:2002 +A2:2008
Warranty	10 Years
Operational Temperature	-5°C to +40°C
Back Box Depth	Dependent On Plate Used
Product Markings	Hot Tap
Neon Indicator	Yes (Red)
Terminal Capacity	4 x 1.5mm ² or 2 x 2.5mm ²
Terminal Torque	1.2Nm
Termination Type	Screw
Terminal Size	4.4mmø
Load Rating	20A
Maximum Voltage	250V 50Hz
Materials	Rocker Switch: Urea Rear Housing: Nylon Switch Cover: Stainless Steel Neon Cover: Polycarbonate Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass
Finish	Pearl Nickel
Aperture Dimensions	32mm (W) x 31.5mm (H)
Dimensions	41mm (W) x 52.5mm (H) x 22mm (D)