

CXT Cable Gland Size Chart - SY Cable

Part Number	Cable Size (mm²)	NOM Dia. (mm)	Number of Cores
20S	0.5	7.4	3
20S	0.5	7.9	4
20S	0.5	8.6	5
20S	0.5	9.2	7
20	0.5	11.6	12
20	0.5	13.4	18
25	0.5	15.5	25
20S	0.75	7.2	2
20S	0.75	7.7	3
20S	0.75	8.3	4
20S	0.75	8.9	5
20S	0.75	9.7	7
20	0.75	12.1	12
25	0.75	15.3	18
25	0.75	16.8	25
20S	1.0	7.6	2
20S	1.0	8.1	3
20S	1.0	8.6	4
20S	1.0	9.7	5
20S	1.0	10.5	7
20	1.0	13.4	12
25	1.0	15.6	18
25	1.0	18.1	25

Part Number	Cable Size (mm²)	NOM Dia. (mm)	Number of Cores
20S	1.5	8.6	2
20S	1.5	9.1	3
20S	1.5	10.1	4
20S	1.5	10.6	5
20	1.5	11.5	7
25	1.5	15.1	12
25	1.5	17.4	18
20S	2.5	10.4	3
20	2.5	11.3	4
20	2.5	12.9	5
25	2.5	13.9	7
25	4.0	13.5	4
25	4.0	14.8	5
25	6.0	15.9	4
25	6.0	17.4	5
32	10	19.1	4
32	10	22.6	5
32	16	22.3	4
50	25	32.5	4
50	35	35.6	4
50	50	38.7	4
50	70	43.8	4

Due to cable diameter variances between manufacturers, we strongly advise the cable diameter is checked where possible, prior to purchasing the products.

CXT Brass Glands

- Tested and approved to BS6121 Pt1
- Supplied in kit form with shrouds, earth tags & steel locknuts
- Suitable for use with all types of screened flexible wire braid/wire braid armoured cables
- Ingress Protection: IP66



Part Number	Description	Gland Size (mm)	Thread Length (mm)	Max Outer Cable Dia. (mm)	Max Inner Cable Dia. (mm)	Armour Wire Dia. (mm)	Pack Qty
QCXT20S	CXT Brass Gland Pack 20mm Small	20	10	11.5	8	0.15/0.35	2
QCXT20	CXT Brass Gland Pack 20mm	20	10	13.5	11	0.15/0.50	2
QCXT25	CXT Brass Gland Pack 25mm	25	10	19.5	16	0.15/0.50	2
QCXT32	CXT Brass Gland Pack 32mm	32	10	19.5	16	0.15/0.55	2
QCXT40	CXT Brass Gland Pack 40mm	40	15	29	23	0.20/0.60	1
QCXT50	CXT Brass Gland Pack 50mm	50	15	37	31.5	0.30/0.80	1
QCXT63	CXT Brass Gland Pack 63mm	63	15	50	42.5	0.30/0.80	1