

ECCLESALL ECCLESALL LED Wall Pack, IP65, 2CCT, LiFePO4 Battery, Anthracite



GENERAL DATA

Light Source	SMD LED
Light Source Replaceable	No
Colour/Finish	Anthracite
Material	Diecast aluminium
Diffuser Type	Prismatic
Diffuser Material	Polycarbonate
IP Rating	IP65
IK Rating	IK10
Mounting Type	Surface
Warranty (Years)	5
Life Time Hours	60,000

BLE LIGHTING AND POWER LTD

Unit 3, Drake Business Park, Drake House Crescent, Sheffield, S20 7HT T: 01246 432325, E: sales@blelighting.co.uk, W: www.blelighting.co.uk This document is uncontrolled if printed, all information is subject to change. Generated on 20/10/23



DIMENSIONS & WEIGHT

Width (mm)	319
Depth (mm)	165
Height (mm)	265
Weight (g)	2172
ELECTRICAL	
Input Voltage (V)	220-240
Input Frequency (Hz)	50
Wattage (W)	13/18/28W
Classification	Class I
Operating Temperature (°c)	0 to +40
Power Factor	0.9
OPTICAL	
Colour Temperature	2CCT
CRI	80
Beam Angle (°)	120
Lumen Output Mains (lm)	1700-3500
EMERGENCY	
Battery Type	LiFePO4 6.4V
Battery Capacity	1.5Ah
Battery Warranty (Years)	3
Recharge Time (hrs)	24
Battery Replaceable	No
Test Procedure	Manual
Emergency Duration (Hrs)	3
Lumen Output Emergency (Im)	275
STANDARDS & APPROVALS	
Manufactured in Accordance with	BS EN 60598-1, BS EN 60598-2-22
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes

BLE LIGHTING AND POWER LTD

Unit 3, Drake Business Park, Drake House Crescent, Sheffield, S207HT T: 01246 432325, E: sales@blelighting.co.uk, W: www.blelighting.co.uk This document is uncontrolled if printed, all information is subject to change. Generated on 20/10/23 I



Accredited Members	ISO 9001, LIA, ICEL
PACKAGING	
Packaging Length (mm)	360
Packaging Width (mm)	300
Packaging Depth (mm)	178

BLE LIGHTING AND POWER LTD

Unit 3, Drake Business Park, Drake House Crescent, Sheffield, S20 7HT T: 01246 432325, E: sales@blelighting.co.uk, W: www.blelighting.co.uk This document is uncontrolled if printed, all information is subject to change. Generated on 20/10/23