

# PANEL HEATERS

## PLE

## Panel heaters with electronic 7-day timer



Model No.	kW	Height x Depth x Width (mm)	Weight (kg)
PLE050(SS)	0.5	430 x 93 x 442	4.0
PLE075(SS)	0.75	430 x 93 x 442	4.0
PLE100(SS)	1	430 x 93 x 614	5.0
PLE125(SS)	1.25	430 x 93 x 720	6.0
PLE150(SS)	1.5	430 x 93 x 720	6.0
PLE200(SS)	2	430 x 93 x 852	6.5

Note: 'SS' denotes stainless steel finish.

### Model No.

PLE

### Features

- With built-in electronic 7-day timer and thermostat.
- Very quiet operation.
- Slimline and clean design.
- Strengthened grilles to increase durability.
- Automatic safety cut-out.
- Splash proof to IP24 for use in bathrooms and other damp areas.
- 4 large control buttons with tactile feedback.
- Optional control panel locking kit (PLK1).
- Hinged wall mounting system for easy installation and decorating.
- Fitted with 1.8m of supply cable.
- Finished in white or stainless steel.

## ELECTRONIC 7-DAY TIMER & THERMOSTAT FEATURES



### PROGRAMMABLE 7-DAY TIMER & THERMOSTAT

Offers a programmable 7-day timer with 6 heating periods per day. Each heating period can be set with different temperature setting.



### HEATING CONTROL SETTINGS

- Comfort heat setting between 15°C to 35°C.
- Setback temperatures can be used for frost protection or maintaining a minimum room temperature between 4°C to 15°C.
- Can set temperatures in degrees Celsius or Fahrenheit.
- Maintains temperature within 0.7 degrees.



### COPY DAY FUNCTION

A copy day function can be used to duplicate the same set of programmes throughout the week.



### ELECTRONIC CHILD LOCK

The digital control panel is designed with an electronic lock to prevent tampering with controls.



### OPEN WINDOW DETECTION

Reacts intelligently to a sudden temperature change in the area or room. When a window or door is opened, the heater recognises the sudden temperature drop and turns the heating off to save energy. When the window or door is closed, the heater automatically detects a temperature rise and switches itself on and resumes normal operation. Once enabled in the setup menu, the open window detection is fully automatic and does not require any human intervention to be activated. Detection time and settings are fully adjustable in the setup menu.



### 4 OPERATING MODES

Programme, Boost, Setback and Manual



### BOOST FEATURE

15-minutes Boost