



Category	Downlights	
Application	Ancillary, Hospitality, Residential, Retail	
Specification	Architectural	

## OCTO Prism Pro Fire Rated Connected by WiZ

OCTO Prism Pro Fire Rated Downlight Connected by WiZ RGBTW Code: APRIP/1/OCTOW/RGBTW







## **PRODUCT FEATURES**

- · IP65 Dimmable LED WiZ enabled tunable white Fire Rated Downlight suitable for residential and commercial applications
- Tunable between 2700K 6500K via WiZ app and voice control offering a choice of 2 outputs, in one luminaire
- Remote driver with 2x1.5mm, + CPC loop-in, loop-out colour coded push fit piano terminals provide an easy and efficient installation
- Fully tested for 30, 60 and 90 minute ceiling types to meet Part B of Building Regulations
- · Connects directly to your WiFi network using Bluetooth technology to support seamless pairing
- New innovative 2 part detachable connector design allows initial wiring and testing to be completed first, then simply plug the downlight back to the connector, ensuring a quick and simple installation
- Low profile design and remote driver allows installation into shallow ceiling voids
- Fully tested to meet Part C (moisture), Part E (acoustic) and Part L (energy) of Building Regulations

GE	eneral information
Wattage	8W
Lumens Delivered	500lm - 550lm (2700K - 6500K)
Lm/W	68lm/w - 75lm/w (2700K - 6500K)
Beam Angle	65
CRI	80
CCT	2700-6500K
Input	220/240V
Operating Temp	-20°C - 35°C
SDCM	6
UGR	25
Cut-Out Size	73mm
Product Weight without Packaging	0.305 kg

Belfast: +44 (0) 2890 773750

Warrington: +44 (0) 1942 433333

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
Fire Rated	Yes	
IP Rating	IP65	
Class Protection	2	
Internal / External	Internal	
Surface / Recessed / Suspended	Recessed	
Lumen Depreciation	L70 54,000h	
Warranty (Years)	5	
CE Mark	Yes	
Diameter	90 mm	
Height	58 mm	











Category	Downlights	
Application	Ancillary, Hospitality, Residential, Retail	
Specification	Architectural	

## OCTO Prism Pro Fire Rated Connected by WiZ RGBTW

Code: APRIP/1/OCTOW/RGBTW







