

Product Code: DPSS30536GY

Luckinslive 433613307

Description: 13A Ingot 2 Gang Zigbee Smart Switched Socket Outlet



UK-PS&TI



General Information

Range		
Plate Dimensions (mm)	146 (W) x 88 (H) x 8 (D)	
Dimensions With Gasket (mm)	149 (W) x 91 (H) x 9 (D)	
Plate Fixing Centres - Horizontal (mm)	120.6	
Style	Rounded Profile	
Finish	Stainless Steel	
Insert Colour	Grey	
Gasket Colour	Grey	
Materials	Front Plate: Stainless Steel Rear Housing: Nylon Terminal Screws: Steel & Yellow Passivated Electronics: PCB & Electronic Components	Insert: Urea Terminals: Brass Internal Busbars: Formed Pressed Brass
Operating Voltage (AC)	250	Frequency (Hz) 50
Resistive Load Rating (A)	13	
Termination Type	Screw	
Terminal Size (mm)	5.7 x 4.8	Terminal Torque Value (Nm) 1.2
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4	
Single Pole Switched	Yes	
3 Pin Safety Shuttered	Yes	
Twin Earth Terminals	Yes	
Protocol	Zigbee	Signal Transmission Frequency 2.4GHz
Open Air Wireless Range (M)	<160	
Standby Current (mA)	1	
Indicator Colour	White & Orange	
Minimum Back Box Depth (mm)	25	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	3	

Standards BS 1363-2, BS EN 61000-6-1, BS EN 61000-6-3, BS EN 60669-2-1 in conjunction with BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
3 pin safety shutter. The shutter will only open once all three plug pins are inserted.
Zigbee signal mesh
Enables manual control (unless locked), wireless control and automated control
Voice control via ClickSmart+ Hub using Alexa and/or Google Home

Components Supplied

Smart Socket Outlet, Fixing Screws, Instruction Manual

Programming Information

With hub and app setup and socket wired and powered, press one of the switches for five to ten seconds, the orange LED indicator starts flashing. Can be paired with hub via app.

