

Product Code: SFSS523GY

Technical Specification

Luckinslive 435275918

Description: 20A Ingot Double Pole Plate Switch With Optional Flex Outlet With Neon







General Information

Insert Dimensions (mm) 82.5 (W) x 82.5 (H) x 2.5 (D)

Plate Dimensions (mm) 86 (W) x 86 (H) x 4 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Screwless Complete

Finish Stainless Steel

Insert Colour Grev

Compatible Cover Plate SCP323#

> Materials Cover Plate: Stainless Steel

Insert: Polycarbonate Rear Housing: Urea Switch Cover: Stainless Steel

Neon Lens: Polycarbonate Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass

Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel

Anti Microbial Certified

Operating Voltage (AC) 250 Frequency (Hz) 50

Resistive Load Rating (A) 20 Termination Type Screw

> Terminal Size (mm) Terminal Torque Value (Nm) 1.8

Terminal Capacity - Solid (mm²) 3 x 2.5 Double Pole Switch Twin Earth Terminals

> Neon Indicator Indicator Colour

Flex Outlet Available

Flex Outlet Location Front of Plate Flex Outlet Dimension (mm) Ø10

Minimum Back Box Depth (mm) 35 Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years)

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal











Specification is subject to change without notice. Errors & Omissions excluded.