

Product Code: SFBK622BK

Technical Specification

Luckinslive 435275484



Description: 20A Double Pole Plate Switch



General Information

Insert Dimensions (mm) 82.5 (W) x 82.5 (H) x 2.5 (D)

Plate Dimensions (mm) 86 (W) x 86 (H) x 4 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Screwless Complete

Finish Matt Black Insert Colour Black

Compatible Cover Plate SCP422#

> Cover Plate: Polycarbonate Materials

Insert: Polycarbonate Rear Housing: Urea Terminals: Brass

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Contacts: Silver "on-lay" Copper / Brass

Earth Strap: Mild Steel

Anti Microbial Certified

Frequency (Hz) 50 Operating Voltage (AC) 250

Resistive Load Rating (A) 20 Termination Type Screw Terminal Size (mm) Ø5

Terminal Torque Value (Nm) 1.8

Terminal Capacity - Solid (mm²) 3 x 2.5 Double Pole Switch Yes Twin Earth Terminals Yes Minimum Back Box Depth (mm)

Ingress Protection

Operational Temperature (°C) -5 to +40 Warranty (Years)

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom

Specification is subject to change without notice. Errors & Omissions excluded.

E: sales@scolmore.com | W: scolmore.com









