c26









121 / 126







157 / 170



158



159

### **RJ11 Telephone Outlets**

115 Single RJ11 (Irish/US) Outlet

# **Telephone Outlets**

120 Single Telephone Outlet - Maste

**121** Twin Telephone Outlet - Master

125 Single Telephone Outlet - Secondary

Twin Telephone Outlet - Secondary

Twin outlets are 2 separate sockets and not internally linked together.

Back Box Depth: 16mm Minimum 115: 35mm Minimum Termination Type: IDC Dimensions: 1 Gang: (88mm x 88mm x 8mm)

Understanding the code

VP - Plate Style <sup>©</sup> BN - Plate Finish 011 - Product No. BK - Insert Colour Please note: AB & BN are only available with black inserts. AB Antique Brass, BR Polished Brass, SB Satin Brass, CH Polished Chrome, SC Satin Chrome, BN Black Nickel, SS Stainless Steel, PN Pearl Nickel, GCBR Georgian Style.

### Satellite Outlets (Unshielded)

156 Non-Isolated Single Satellite Outlet

157 Isolated Satellite & Isolated Coaxial Outlet

Non-Isolated Satellite & Non-Isolated

Isolated outlets will filter out any interference, if a 2 way signal is required, i.e. for use with satellite hard wire extensions, then a non-isolated outlet is required.

### Non-Isolated Coaxial Outlets (Unshielded)

O65 Single Coaxial OutletO66 Twin Coaxial Outlet

## Isolated Coaxial Outlets (Unshielded)

158 Single Isolated Coaxial Outlet159 Twin Isolated Coaxial Outlet

Back Box Depth: 16mm Minimum Dimensions: 1 Gang: (88mm x 88mm x 8mm)

Understanding the code

VP - Plate Style BN - Plate Finish 011 - Product No. BK - Insert Colour Please note: AB & BN are only available with black inserts. AB Antique Brass, BR Polished Brass, SB Satin Brass, CH Polished Chrome, SC Satin Chrome, BN Black Nickel, SC Statinless Steel, PN Pearl Nickel, GCBR Georgian Style