

COMMANDO

DIMMABLE HIGH BAYS

Our Commando range of dimmable, excellent efficiency high bays are suitable for any high mounting application projects. The range includes emergency options, plus a wide choice of automatic lighting controls for maximum efficiency.



Features

- High efficiency up to 145 lm/W
- Wide supply voltage range 100-277V suitable for site lighting and other applications
- Meanwell 1-10V dimmable driver
- Optional refractor attachment (order separately)
- Built-in resettable surge protection



Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
COMHMB100BD-2	LED Compact Dimmable High Bay	13,000 lm		100W	130 lm/W

Product Information

Guarantee	5 Years
Colour Appearance (CCT)	6500K
IP Rating	IP65
IK Rating	IK10
Voltage	100-277V
Material (Body/Housing)	Die-Cast Aluminium
Material (Diffuser/Cover)	Polycarbonate
Colour Rendition (CRI)	Ra > 80

Colour Finish	Black
LED Life Expectancy	L80B50 50,000 Hours
Power Factor	>0.93
Frequency	50/60Hz
Driver Type	1 - 10V Dimmable
Approval	UKCA CE
Electrical Class	Class I
Working Temperature	-30°C to 50°C



COMMANDO

DIMMABLE HIGH BAYS

Packaging Information

Dimensions (mm)	Ø: 252 x D: 200 mm
Product Net Weight (kg)	3.4 kg
Barcode	5055807620161
Box Dimensions (mm)	L: 310 x W: 310 x D: 215 mm
Box Gross Weight (kg)	4.2 kg

Units/Outer Carton	2
Outer Carton Barcode	15055807620168
Outer Carton Dimensions (mm)	L: 450 x W: 340 x D: 340 mm
Outer Carton Gross Weight (kg)	9.4 kg

