



LED PANEL 620x620

Indoor LED recessed ceiling light white 3000K
UGR<19

The LED PANEL 620 comes in several different light colours for grid ceilings and provides a modern and space-saving solution for an efficient kind of base lighting. You achieve a pleasant, homogeneous and glare-free lighting sensation with this product, with an aperture angle of less than 19°.

TECHNICAL DATA

Item no.	1003073
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling, Ceiling with Acc.
Secondary power / voltage	1050 mA
Safety class	III
Lumen	4000 lm
Colour temperature	3000 Kelvin
Beam angle	120 °
Color	white
CRI	90
UGR ≤	19
LXXBXX data	L70B50
Service life	50000 h
Light distribution	axis symmetric
Light outlet	direct
Risk Group	1
Length	61.7 cm
Width	61.7 cm
Height	0.9 cm
Net weight	3.297 kg
Gross weight	4.163 kg

Light Source

916571	
--------	---

Accessories

1002425	LED driver MEDO 600 , dimmable DALI/1-10V
158791	CEILING PLATE , for LED PANEL, I-VIDUAL and I-VIDUAL LED PA- NEL, white
158799	SUSPENSION SET , for LED PANEL, I-VIDUAL and I-VIDUAL LED PA- NEL, steel wire and Y-wire suspension
464804	LED DRIVER , 40W, 1050mA, triac dimmable

Shape of cut-out	square
Installation depth	5 cm
BIG WHITE Page	419