



Features & Benefits

- Conforms to TIA/EIA-568-C Category 6 Specification
- Conforms to IEC 60332-1, IEC 61034 and IEC 60754
- Available from stock in lengths from 0.5 to 5 metres
- Available in nine different colours
- Each lead is individually tested
- Plugs conform to ISO8877

Specification

Plug	High performance modular plug
Cable	26 AWG LSZH Category 6 stranded cable
Cable Diameter	Approx. 4.8mm
Conforms to	TIA/EIA-568-C Category 6 Specification

Ordering Information

Colour	Length (metre)	Part Number	Length (metre)	Part Number
Grey	0.5m	003-385-005-01B	1m	003-385-010-01B
White	0.5m	003-385-005-02B	1m	003-385-010-02B
Blue	0.5m	003-385-005-03B	1m	003-385-010-03B
Green	0.5m	003-385-005-04B	1m	003-385-010-04B
Red	0.5m	003-385-005-05B	1m	003-385-010-05B
Yellow	0.5m	003-385-005-06B	1m	003-385-010-06B
Orange	0.5m	003-385-005-07B	1m	003-385-010-07B
Purple	0.5m	003-385-005-08B	1m	003-385-010-08B
Black	0.5m	003-385-005-09B	1m	003-385-010-09B
Grey	2m	003-385-020-01B	3m	003-385-030-01B
White	2m	003-385-020-02B	3m	003-385-030-02B
Blue	2m	003-385-020-03B	3m	003-385-030-03B
Green	2m	003-385-020-04B	3m	003-385-030-04B
Red	2m	003-385-020-05B	3m	003-385-030-05B
Yellow	2m	003-385-020-06B	3m	003-385-030-06B
Orange	2m	003-385-020-07B	3m	003-385-030-07B
Purple	2m	003-385-020-08B	3m	003-385-030-08B
Black	2m	003-385-020-09B	3m	003-385-030-09B
Grey	4m	003-385-040-01B	5m	003-385-050-01B
White	4m	003-385-040-02B	5m	003-385-050-02B
Blue	4m	003-385-040-03B	5m	003-385-050-03B
Green	4m	003-385-040-04B	5m	003-385-050-04B
Red	4m	003-385-040-05B	5m	003-385-050-05B
Yellow	4m	003-385-040-06B	5m	003-385-050-06B
Orange	4m	003-385-040-07B	5m	003-385-050-07B
Purple	4m	003-385-040-08B	5m	003-385-050-08B
Black	4m	003-385-040-09B	5m	003-385-050-09B

Connectix Category 6 UTP Patch Leads are designed to exceed the performance requirements of the Category 6 Specification.

The low flammability, low smoke production and zero halogen sheath make these patch leads the ideal choice in public buildings and other fire sensitive areas.

Connectix Patch Leads are made from Category 6 stranded cable and are terminated using high performance modular plugs. There are a variety of leads in lengths from 0.5 to 5 metres in stock as well as a number of different colours.

