

Circulation corridor (continued)

Secondary lighting



Solis

600 x 600mm panel



Code : P2A16S30WA
30W | 3450lm | 4000K

Code : P4A19S40W
40W | 4320lm | 4000K



WL94

Halo lit effect



Code : WL9418SCS
(switchable)

18W
1800lm | 2000lm
3000K | 4000K | 6500K



Stairs & landing

Secondary lighting



WL95

IK10 & IP65



Code : WL9515SCS
(switchable)

10W | 15W
1100lm | 1650lm | 1800lm
3000K | 4000K | 6500K



Caiman 5ft twin

Colour switchable



Code : AC5TN (switchable)
50W

5750lm | 6250lm | 6500lm
3000K | 4000K | 6500K



Shower rooms

Secondary lighting



H2 Pro Extreme

Corrosion & waterproof



Code : DL48938MW30
5W | 460lm | 3000K

Code : DL48938MW40
5W | 490lm | 4000K



Emergency lighting

Emergency lighting



Salvus bolt

Emergency conversion

Compatible with Borealis & Caiman



Code : EMBOLTMOPEN
Manual-test for open area

Code : EMBOLTMCOR
Manual test for corridors



Salvus bolt

Emergency conversion

Compatible with Borealis & Caiman



Code : EMBOLTSOPEN

Self-test for open area

Code : EMBOLTCOR
Self-test for corridors



Salvus blade

For direction



Code : EMBL30M
Manual-test

Code : EMBL30S
Self-test



Salvus exit

For internal exit doors



Code : EMBX35M
Manual-test

Code : EMBX35S
Self-test



Salvus bulkhead

For external exit doors



Code : EMBH145M
Manual-test

Code : EMBH145S
Self-test



Salvus route

For escape routes



Code : EMER120M035
Manual-test for open area

Code : EMRWST
Self-test for open area
& corridors



Salvus twin spot

75° Tilttable 145° Rotatable



Code : EMTW400S
Self-test

