

Product Code: DPSS426GY

Technical Specification

Luckinslive 422428574

Description: 2 Gang MiniGrid® Unfurnished Plate - 6 In-Line Apertures







Insert: Urea

Terminal Screws: Steel & Yellow Passivated

General Information

Plate Dimensions (mm) 146 (W) x 88 (H) x 8 (D)

Dimensions With Gasket (mm) 149 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm) 120.6

MiniGrid Plate (Gang) 2

MiniGrid Single Width Module Quantity

MiniGrid Double Width Module Quantity

Rounded Profile Style Stainless Steel Finish

Insert Colour Gasket Colour Grey

> Materials Front Plate: Stainless Steel

Terminals: Brass

Earth Strap: Mild Steel

Anti Microbial Certified No

Termination Type Screw Modular Rocker Switches

Minimum Back Box Depth (mm) Dependent On Modules Fitted

IP20 Ingress Protection

Operational Temperature (°C) -5 to +40

Warranty (Years)

Standards BS 5733

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Interchangeable with modules in the MiniGrid Range.













Specification is subject to change without notice. Errors & Omissions excluded.