




GRP Enclosure Dimensions

References	Rows	Dimensions (mm)						Inside Fixing		Outside Fixing		
		A	H	B	C	D	E	F	E1	E2	F1	F2
FL201B	1	250	300	160	-	-	-	-	-	-	-	-
FL204B	2	300	350	160	250	300	219	258	339	339	269	389
FL209B	3	300	500	200	250	450	219	408	339	339	419	539
FL213B	3	400	500	200	350	450	319	408	439	439	419	539
FL216B	4	400	650	200	350	600	319	558	439	439	569	689
FL221B	4	500	650	250	450	600	419	558	539	539	569	689
FL229B	5	600	800	300	550	750	519	708	639	639	719	839
FL327B	-	850	1200	300	750	1050	-	-	-	-	-	-

Torque Settings

			Cables >1.5mm² Tightening torque (N.m)		Cables ≤1.5mm² Tightening torque (N.m)		Cable Stripping (mm)
	Pz No.	(mm)	Single Cable	Multi Cables	Single Cable	Multi Cable	
Consumer unit terminals							
Earth and neutral terminal bars	2	6.5	2	2	1.5	1.5	10
Isolation							
SB switch disconnectors	2	6.5	3.6	3.6	3.6	3.6	15
Circuit protection							
MTN MCB	2	6.5	2.8	2.8	2.8	2.8	13
NBN/NCN/NDN MCB	2	6.5	2.8	2.8	2.8	2.8	13
RCBO	2	5.5	2.1	2.1	2.1	2.1	13
RCCB	2	5.5	2.8	2.8	2.8	2.8	13