

Bulkheads



CCT switchable between 3000K, 4000K & 5000K




Market leading up to 165lm/W efficacy



Integral photocell as standard

Guarantee	5 years
Wattage	10W or 17W
IP rating	IP66
Dimmable	No
Input	220-240V 50/60Hz
LED lifetime	54,000h L70
Emergency version available	Yes
Sensor available	PC Dusk to Dawn
Install connector type	Push-fit terminal, loop-in/loop-out
Ambient temperature	-30°C to +50°C
Electric class	1



Arc 10W & 17W

Wallpack suitable for 3m (10W) or 4m (17W) mounting height

2 year
on site
guarantee



Product code	Finish	Type	Wattage	Colour	Beam	lm	lm/W	Em lm
ARA1N	Anthracite grey RAL7016	Standard	10W	3000K	98°*114°	1550	155	-
				4000K	98°*114°	1650	165	-
				5000K	98°*114°	1600	160	-
ARA1NE	Anthracite grey RAL7016	Emergency	10W	3000K	98°*114°	1550	155	300
				4000K	98°*114°	1650	165	300
				5000K	98°*114°	1600	160	300
ARA2N	Anthracite grey RAL7016	Standard	17W	3000K	98°*114°	2600	153	-
				4000K	98°*114°	2750	162	-
				5000K	98°*114°	2700	159	-
ARA2NE	Anthracite grey RAL7016	Emergency	17W	3000K	98°*114°	2600	153	300
				4000K	98°*114°	2750	162	300
				5000K	98°*114°	2700	159	300