

COMMANDO PLUS

WATTAGE & CCT SELECTABLE HIGH BAYS

Commando Plus is the latest generation of the popular Commando high range. Suitable for any high mounting application, features both selectable wattage and colour appearance, offering maximum flexibility. The range delivers excellent efficacy of 140lm/W and is fully dimmable 0-10V.



Features

- High efficacy 140lm/W as standard
- Wattage and CCT selectable
- Plug in microwave sensor - RC setup
- 110° beam angle as standard – optional 90° lens
- Wide range of refractor and reflector accessories
- High output self test emergency kit option

Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
COM150-CCT	Commando Plus High Bay Selectable Wattage 100-150W & Selectable CCT 4000/5200/6500K	21000 lm		100/125/150W Selectable	140 lm/W

Product Information

Guarantee	5 Years
On-Site Warranty	2 Years
Colour Appearance (CCT)	4000/5200/6500K Selectable
IP Rating	IP65
IK Rating	IK08
Voltage	120-277V
Material (Body/Housing)	Die-Cast Aluminium
Material (Diffuser/Cover)	Polycarbonate
Colour Rendition (CRI)	Ra > 80

Colour Finish	Black RAL 9017
LED Life Expectancy	L70B50 >50,000 Hours
Power Factor	0.95
Frequency	50/60Hz
Driver Type	0-10V Dimmable
Approval	UKCA CE
Electrical Class	Class I
Working Temperature	-40°C to 50°C



COMMANDO PLUS

WATTAGE & CCT SELECTABLE HIGH BAYS

Packaging Information

Dimensions (mm)	Ø: 276 x D: 134 mm
Product Net Weight (kg)	2.3 kg
Barcode	5055807625067
Box Dimensions (mm)	L: 292 x W: 105 x D: 290 mm
Box Gross Weight (kg)	2.5 kg

Units/Outer Carton	5
Outer Carton Barcode	15055807625064
Outer Carton Dimensions (mm)	L: 560 x W: 301 x D: 315 mm
Outer Carton Gross Weight (kg)	13.2 kg



Maximum Fittings Per Circuit

Automatic Circuit Breaker Type:	B6	B10	B13	B16	B20	C10	C13	C16	C20
Rated Current:	6A	10A	13A	16A	20A	10A	13A	16A	20A
Cable (mm):	1.5	1.5	1.5	2.5	2.5	1.5	1.5	2.5	2.5
COM150-CCT	6	10	12	16	20	16	21	27	33
COM200-CCT	3	5	6	8	10	8	10	13	16
COMPRO200	3	5	6	8	10	8	10	13	16

