

Can also be used with LED lamps
See Page 55-57

TRADITIONAL RECESSED LIGHTING


See page 48-49 for LED Recessed Section

Neat and discreet lighting solutions
for ceilings and walls with voids

IP65 FIRE RATED 50W MAX GU10 SHOWER LIGHTS

- This luminaire is compatible with bulbs of the energy classes: A++ to E
- Requires 1 x 240V GU10 lamp (not included)
- Fittings are rated at 50W max
- 3 way large terminal block with cable restraint for easy installation with ample space for loop in, loop out wiring
- Separately tested for 30, 60 and 90 minute ceiling types to meet standard BS476 Part 21
- Silicon bezel gaskets seal against air permeability
- Hole cut out size: 65mm
- M.O.M: 1 / O.P.Q: 10

Code	Colour
FIREIPCR	Polished Chrome
FIREIPSN	Satin Nickel
FIREIPWH	White



IP65 MAINS 50W MAX SHOWER LIGHTS

- Requires 1 x GU10 energy saving lamp (not included). Fitting is rated at 50W max
- This luminaire is compatible with bulbs of the energy classes: A++ to E
- Sprung bezel pulls off to facilitate easy lamp change
- Can be used in bathroom zones 1 & 2
- Hole cut out size: 70mm
- Steel construction
- M.O.M: 5 / O.P.Q: 50

Code	Colour
SLGU CR	Polished Chrome
SLGU SN	Brushed Nickel
SLGU WH	White



IP20 50W MAX MAINS / LOW VOLTAGE CEILING DOWNLIGHT CONVERTERS

- This luminaire is compatible with bulbs of the energy classes: A++ to E. Fitting is rated at 50W max
- Pressed steel construction
- Supplied with ceramic GU10 & GU5.3 lampholders
- Hole cut out 70-140mm: replaces a wide range of outdated downlights
- Shallow profile: neat, unobtrusive solution
- Converts traditional mains R50, R64 and R80 downlight and eyeball dimensions to modern GU10 or low voltage lighting: allows use of modern light source without expensive repairs & decoration
- M.O.M: 5 / O.P.Q: 40

Code	Colour
CR80BS	Polished Brass
CR80CR	Polished Chrome
CR80SN	Brushed Nickel
CR80WH	White

