

IP66 LED STANDARD / EYELID DIFFUSER AMENITY CEILING / WALL LIGHTS

ALL FITTINGS: 12W / 4200K / 800 lm / 25,000 hrs / IP66 / A Rated

Long life, energy efficient utility fitting perfect for domestic or commercial settings including perimeter lighting, paths, gardens and porches, communal areas, staircases and many more.

- Polycarbonate / ABS construction
- Multiple low power LED array & optically optimised diffuser: ensures a soft, even lighting effect with no degradation of light output
- Stainless steel screws
- 4200K colour temperature: for bright neutral white appearance
- IP66 ceiling or wall mounted
- M.O.M: 1 / O.P.Q: 10

MICROWAVE VERSIONS:


- Adjustable microwave sensor: with options to adjust 2-50 lux or disable, detection range 10-100% and time 5 secs - 15 mins
- The microwave sensor is discreetly placed behind the diffuser: making it unobtrusive so there is no compromise to the appearance of the fitting or the room design



Code	Diffuser	Colour
SHFULLBK	Standard	Black
SHFULLWH		White
SHEYEBK	Eyelid	Black
SHEYEW		White

MICROWAVE VERSIONS BELOW:

SHFULLMWBK	Standard	Black
SHFULLMWWH		White
SHEYMWBK	Eyelid	Black
SHEYMWWH		White





IP66 LED MINI AMENITY FITTINGS

ALL FITTINGS: 6W / 4200K / 35,000 hrs / IP66 / A Rated

Long life, energy efficient utility fitting perfect for domestic or commercial settings including pathway illumination, gardens and porches, staircases and many more.

- Polycarbonate construction
- Multiple low power LED array & optically optimised diffuser: ensures a soft, even lighting effect with no degradation of light output
- Instant start to full illumination level
- Stainless steel screws
- 4200K colour temperature: for bright neutral white appearance
- IP66 ceiling or wall mounted: giving versatile fixing options suitable for bathroom, internal and external use
- M.O.M: 1 / O.P.Q: 10




Code	Version	Colour
MINIFULLBK	Standard 380 lm	Black
MINIFULLWH		White
MINIEYEBK	Eyelid 330 lm	Black
MINIEYEW		White



IP54 LED 18W CEILING/WALL LIGHT

White / 18W / 4000K / 1600 lm / 30,000 hrs / IP54 / A+ Rated



- Polycarbonate construction
- Multiple low power LED array & optically optimised diffuser
- IP54 ceiling or wall mounted
- M.O.M: 1 / O.P.Q: 8

