


**VITM4-SELVMOD**

See page 96  
for An-10 options



Switching Module.  
To be used for manual switching only – no detector

Order Code	Description
<b>VITM4-SELVMOD</b>	Switching module – simple connection of switches using SELV removes the need for RCD protection. Includes integral time delay feature

**Dimensions****Luminaire Leads & Connectors Switching**

Connectors can  
be configured as  
rear or side entry

**PATENTED DESIGN**

Order Code	Description
<b>VITM4L303100W</b>	3 core luminaire lead (white), 1.0mm <sup>2</sup> , (3 metres)
<b>VITM4L305100W</b>	3 core luminaire lead (white), 1.0mm <sup>2</sup> , (5 metres)
<b>VITM4L403100R</b>	4 core luminaire lead (red), 1.0mm <sup>2</sup> , (3 metres)
<b>VITM4L405100R</b>	4 core luminaire lead (red), 1.0mm <sup>2</sup> , (5 metres)
<b>VITM4-LPW</b>	4 pole luminaire connector (white)
<b>VITM4-LPR</b>	4 pole luminaire connector (red)


Other cable lengths are available upon request

**i Order Code Guidelines for Cables**

Prefix	Poles	Lead	Core	Length in Metres	Cable Area	Type	Plug Colour
<b>VITM</b>	4	L	3/4	03 or 05 (other lengths to order)	1.0mm <sup>2</sup> (1.5mm <sup>2</sup> to order)	0 = Isf	W (White) or R (Red) B (Black) to order

**Ceiling Rose**

Order Code	Description
<b>VITM-ROSE</b>	Ceiling rose with connector plug. BESA box not included. Power Rating of system 16A (at 230VAC)
<b>VITM-ROSE-R</b>	Ceiling rose with Red connector plug. Suitable for emergency fittings. BESA box not included. Power Rating of system 16A (at 230VAC)
<b>VITM-ROSE-NP</b>	Ceiling rose, no connector plug. BESA box not included. Power Rating of system 16A (at 230VAC)

**Dimensions****Dual Detector Leads**




Order Code	Description
<b>VITM4-LD3-PRM*</b>	Dual detector lead for two PRM detectors (3 metre)
<b>VITM4-L3-PRM*</b>	Detector lead for single PRM detectors (3 metre)

\*Only for single channel detectors.

Marco Basket Fixing Clip



Order Code	Description
VITM-MCFUSC	VITM Marco basket fixing clip



	Order Code	Description
	UNLCDHS	Professional commissioning handset
	UHS5	Commissioning handset
	UHS7	User handset

PROGRAM FROM GROUND LEVEL



The IR transmitting and receiving technology in our handsets and detectors has been carefully designed to allow programming from ground level.

Luminaire Leads & Connectors Switching



Connectors can be configured as rear or side entry

PATENTED DESIGN

Order Code	Description
VITM4L303100W	3 core luminaire lead (white), 1.0mm <sup>2</sup> , (3 metres)
VITM4L305100W	3 core luminaire lead (white), 1.0mm <sup>2</sup> , (5 metres)
VITM4L403100R	4 core luminaire lead (red), 1.0mm <sup>2</sup> , (3 metres)
VITM4L405100R	4 core luminaire lead (red), 1.0mm <sup>2</sup> , (5 metres)
VITM4-LPW	4 pole luminaire connector (white)
VITM4-LPR	4 pole luminaire connector (red)

Other cable lengths are available upon request