



HMD199T

MCBs 80 - 125A 15kA D Curve

Curves D

15 kA BS EN 60898-1
15 kA BS EN 60947-2

Use

Commercial and industrial applications.

KEMA

Approved according to BS EN 60898-1

I_n 80 to 125A

Tripping Curves

"D" magnetic setting between 10 to 20 I_n .

Connection Capacity

- 35mm² flexible wire (50mm² possible with some cable pin lugs)
- 70mm² rigid wire



HMD299T

Single Pole MCBs 15kA D Curve

Rating	Width (26.25mm)	Cat ref.
80A	1 ½ Mod	HMD180T
100A	1 ½ Mod	HMD190T
125A	1 ½ Mod	HMD199T



HMD399T

Double Pole MCBs 15kA D Curve

Rating	Width (52.5mm)	Cat ref.
80A	3 Mod	HMD280T
100A	3 Mod	HMD290T
125A	3 Mod	HMD299T



HMD499T

Triple Pole MCBs 15kA D Curve

Rating	Width (78.75mm)	Cat ref.
80A	4 ½ Mod	HMD380T
100A	4 ½ Mod	HMD390T
125A	4 ½ Mod	HMD399T

Four Pole MCBs 15kA D Curve

Rating	Width (105mm)	Cat ref.
80A	6 Mod	HMD480T
100A	6 Mod	HMD490T
125A	6 Mod	HMD499T