

Technical Specification

Product Code: GM2047PWSB      Description: 13A Fused Connection Module



General Information

|                         |                                                                                                                                                    |
|-------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| Dimensions              | 24.5mm (W) x 50mm (H) x 25mm (D)                                                                                                                   |
| Aperture Dimensions     | 20mm (W) x 35mm (H)                                                                                                                                |
| Module Frame Finish     | Polar White                                                                                                                                        |
| Module Finish           | Satin Brass                                                                                                                                        |
| Materials               | Body & Insert: Nylon<br>Insert Cover: Stainless Steel<br>Internal Busbars: Brass<br>Terminals: Brass<br>Terminal Screws: Steel & Yellow Passivated |
| Maximum Voltage         | 250V 50Hz                                                                                                                                          |
| Load Rating             | 13A                                                                                                                                                |
| Terminal Size           | 5mmø                                                                                                                                               |
| Termination Type        | Screw                                                                                                                                              |
| Terminal Torque         | 1.2Nm                                                                                                                                              |
| Terminal Capacity       | 3 x 2.5mm <sup>2</sup> or 1 x 4mm <sup>2</sup>                                                                                                     |
| Product Markings        | Fused Symbol                                                                                                                                       |
| Fuse Fitted             | 13A (BS 1362)                                                                                                                                      |
| Back Box Depth          | Dependent On Plate Used                                                                                                                            |
| Operational Temperature | -5°C to +40°C                                                                                                                                      |
| Warranty                | 10 Years                                                                                                                                           |
| Standards               | BS 1363-4: 2016 +A1: 2018<br>BS 1362:1973                                                                                                          |

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.