

ARCHITECTURAL DOWNLIGHTS SPECIFICATION SHEET



BDL10F30MD

Sleek, low glare, baffled downlight

FEATURES

IP rating	IP44
Colour flexibility	Fixed colour
Tilttable	Fixed
Rotation angle	Fixed
UGR	0
Dimmable	DALI 2 Dimming
Input	220-240V 50/60Hz
LED Lifetime	70,000h L70 B10
CRI	>90Ra
SDCM	3SDCM
Flicker Free	Yes
Emergency version available	Yes

INSTALLATION INFORMATION

Install Connector Type	Loop in, loop out
Insulation Coverable	No
Cut Out Size	65-68mm
Bathroom zone	1
Inrush Current	20A 17µs
Construction Material	Aluminium
Maximum ceiling thickness	40mm
Weight	240g
Maximum ambient temperature	40°C
SELV	Yes
Building regulations	Part P, L, C, E
Electric Class [1, 2, 3]	2

PHOTOMETRICS @ 25°C

Product code	Finish	Feature I	Feature II	Feature III	Wattage	Colour	Beam angle	lm	lm/W	lx @ 1m
--------------	--------	-----------	------------	-------------	---------	--------	------------	----	------	---------

BDL10F30MD	Matt White RAL9003	Downlight	Black Baffle	Slim Round Bezel	9.6W	3000K	24°	640	67	3191
------------	--------------------	-----------	--------------	------------------	------	-------	-----	-----	----	------

WIRING INFORMATION

Cable Required for Connector	1047 x twin & earth (6242Y 3x1.5mm²) or 3-core cable (R02V 3x1.5mm²)
Type of Wiring Required	Parallel

ACCESSORIES

LEDEP10	3hr non-maintained, self-test emergency pack (plug & play)	Sold Separately
BDLFH2	Fire hood	Sold Separately



COLLINGWOOD  
LIGHTING

01604 495 151  
collingwoodlighting.com

- /collingwoodlighting
- /collingwoodlighting
- collingwoodled

GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

Black baffle & CRI 90+ for a low glare and high-quality appearance, showing colours and textures in their best light.

Choice of fixed or adjustable function, allows you to direct light exactly where it is required.

Mains, 1-10V or DALI dimming options for flexibility and integration with control systems.

Comes with rolled spring clips and plug & play connectors to support ease of installation.

7 year warranty: Collingwood's signature quality you can trust.

Medium beam angle, excellent for corridor lighting.

Slim and discreet flat metal bezel.

Light source  
energy efficiency:



Beam angle:

