Xnightsbridge

DATASHEET




EL6060

230V IP20 595x595 23W/33W CCT Adjustable Troffer

Panel

www.mlaccessories.co.uk



MLA PART CODE	EL6060
DESCRIPTION	230V IP20 595x595 23W/33W CCT Adjustable Troffer Panel
NET WEIGHT (KG)	3.09
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 595 Width - 595 Depth - 70
CONSTRUCTION	Construction - Pressed steel Construction 2 - & polycarbonate
CLASS	I
IP RATING	IP20
WATTAGE (W)	33
LAMP TECHNOLOGY	SMD LED
LUMENS (LM)	4500
LUMENS LIGHT SOURCE ONLY (LM)	5470
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	163
CIRCUIT WATTAGE (W)	32.7
ССТ	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.15
DISPLACEMENT FACTOR	>0.9
SVM	0.6
PST-LM	0.03
L70B50 LIFESPAN (HRS)	60000
DIMMABLE	No
OPERATING TEMPERATURE	25°C





Xnightsbridge

INPUT VOLTAGE	230V 50Hz
DRIVER	DRIVER TYPE - Constant Voltage MAX. OUTPUT - 39W OUTPUT VOLTAGE - 30-43V OUTPUT CURRENT - 630/900mA EFFICIENCY FULL LOAD - 90 AMBIENT TEMPERATURE (Ta)20~+50°C CASE TEMPERATURE (Tc) - 75°C
WARRANTY	5year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270865820

Date Created: 08/01/2024 21:07





