


Product Code: SFSS536PW

Technical Specification

Luckinslive 435275154

Description: 13A Ingot 2 Gang Double Pole Switched Socket Outlet







Insert: Polycarbonate

Switch Cover: Stainless Steel

Frequency (Hz) 50

Terminal Torque Value (Nm) 2

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

General Information

Insert Dimensions (mm) 142.5 (W) x 82.5 (H) x 2.5 (D)

Plate Dimensions (mm) 146 (W) x 86 (H) x 4 (D)

Plate Fixing Centres - Horizontal (mm) 120.6

Style Screwless Complete

Finish Stainless Steel

Insert Colour Polar White

Compatible Cover Plate SCP436#

Materials Cover Plate: Stainless Steel

Rear Housing: Urea

Terminals: Brass

Contacts: Silver "on-lay" Copper / Brass

Earth Strap: Mild Steel

Anti Microbial Certified

Operating Voltage (AC) 250

Resistive Load Rating (A) 13

Termination Type Screw Terminal Size (mm)

3 x 2.5 or 2 x 4

Terminal Capacity - Solid (mm²)

Double Pole Switch

Twin Earth Terminals

Minimum Back Box Depth (mm)

Ingress Protection

Operational Temperature (°C) -5 to +40

Warranty (Years) 20

Standards BS 1363-2

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal











Specification is subject to change without notice. Errors & Omissions excluded.