

Product Code: DPMB500BK

Technical Specification

Luckinslive 435284006





Description: 45A Ingot 1 Gang Double Pole Plate Switch



General Information

Plate Dimensions (mm) 88 (W) x 88 (H) x 8 (D)

Dimensions With Gasket (mm) 91 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Rounded Profile Finish Matt Black

Insert Colour Black Gasket Colour Black

> Materials Front Plate: Stainless Steel

Switch Cover: Stainless Steel

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Insert & Rear Housing: Urea

Terminals: Brass

Terminal Torque Value (Nm) 2.5

Contacts: Silver "on-lay" Copper / Brass

Earth Strap: Mild Steel

Anti Microbial Certified

Operating Voltage (AC) Frequency (Hz) 50 250

Resistive Load Rating (A) 45 Termination Type Screw Terminal Size (mm) Ø6

Terminal Capacity - Solid (mm²) 1 x 16

Double Pole Switch Yes

Twin Earth Terminals Yes

Product Marking On & Off

Minimum Back Box Depth (mm) 35

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years)

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Supplied with Matt Black plate fixing screws.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.













Specification is subject to change without notice. Errors & Omissions excluded.